

**TF229: AIR TO COIL CONVERSION – DISCOVERY 2****2" LIFT – MEDIUM LOAD SPRINGS & +2" LONGER PRO SPORT SHOCK ABSORBERS  
FRONT & REAR****FITTING INSTRUCTIONS**

1. Put the car into gear or park and apply the hand brake, loosen the front wheel nuts on one side, raise the vehicle on a trolley or bottle jack under the axle and then support the vehicle with an axle stand under the chassis. It's easier and safer to do this job one side at a time.
2. Remove the front wheel.
3. Undo the 2 bolts securing the bottom of the shock absorber.
4. Gently lower the axle on the jack, the axle will lower the spring away from the chassis and the spring will become loose. Once this happens stop lowering the axle. Take care not to stretch the brake lines.
5. Undo the 4 nuts securing the shock absorber turret to the chassis bracket then Pull the turret and shock absorber out through the hole in the inner wing.
6. Undo and remove the bolt through the top of the shock absorber and then remove the shock absorber from the turret.
7. Fit the new shock absorber in to the turret, and then replace and tighten the top bolt
8. Clean the spring plate on the axle and fit the new spring ensuring you use the correct spring for the side of the vehicle you are changing as the springs are normally handed.
9. Gently raise the axle back up using the jack and ensuring the spring relocates into the top chassis mount.
10. Lower the turret and shock absorber back through the hole in the inner wing fit the washers and nuts and tighten down the turret onto the chassis bracket.
11. Pull the lower part of the shock down to the spring seat and re-fit and tighten the 2 bottom securing bolts
12. Refit the wheel, lower the car off of the axle stand and torque the wheel nuts correctly.
13. Repeat the procedure on the other side.
14. Using an Autologic or Test Book, depressurise the air suspension.
15. Lift the rear of the Discovery and use axle stands to support the vehicles chassis.
16. Remove the wheels and use to support the axle.
17. Remove clips from air spring then push down on spring and take off the air line. Take care of compressed air.
18. Turn spring and remove from the axle.

WARRANTY & DISCLAIMER - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fitment or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Ltd. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.



19. Find the 2 holes for the spring seat retaining bolts. To facilitate an easy installation, run a 10mm x 1.5 tap through these holes.
20. Place lower spring seats into position.
21. Jack up the axle to remove the tension from the shock absorber. Take away the lower bolt and disconnect the ABS sensor lead from the bracket.
- 22.
23. Undo the nut on the bolt that goes through the top of the shock absorber and the bracket on the chassis and then remove the bolt.
24. Refit the bolt through the top of the new shock absorber and through the bracket on the chassis and then refit and tighten the nut
25. Place the upper spring isolator to the top of the spring. The tighter coils of the spring should be at the top.
26. Lower the axle so the spring can be installed.
27. Raise the axle ensuring the spring stays in place. Refit the bolt through the top of the new shock absorber and through the bracket on the chassis and then refit and tighten the nut. Reconnect the ABS sensor lead.
28. Repeat procedures for the other side of the Discovery.
29. When both sides are done refit wheels lower the car off of the axle stands and torque the wheel nuts correctly.
30. Use the Autologic or Test book to disable the air springs by reprogramming the ECU to coil springs.



**WARRANTY & DISCLAIMER** - Terrafirma products are warranted free from defects in materials and workmanship for a period of 12 months from the date of retail invoice. Terrafirma does not warrant that the products manufactured or marketed by it comply with the laws of the country where those goods are purchased or used. It is the sole responsibility of the purchaser to ascertain whether products being purchased, or the fitting of those products to any other object, comply with local laws. This warranty covers structural defect and workmanship but does not cover finishes, labour charges for removal or refitting, freight costs, accident damage, misuse or abuse, damage due to incorrect or improper fitment or application, modified product, faulty design or consequential damage of any kind. Damage or defects caused by collision, alteration, improper installation, road hazards, adverse conditions or usage for any other purpose other than normal private usage are not covered by this warranty. Terrafirma shall not be liable for any other claim relating to the use of the product and any indirect special or consequential damage or injury to any person, company or other entity. All claims must be accompanied by the original retail invoice and should be submitted to the supplying Allmakes 4x4/Terrafirma distributor. This warranty covers only the replacement of the product or part concerned. The decision remains solely at the discretion of Allmakes Ltd. The information contained in this catalogue was correct at the time of going to press. Allmakes/Terrafirma and its associated companies reserve the right to alter the range and any product specifications without notice. Always consult your Allmakes/Terrafirma distributor for the latest product information and specifications. The Terrafirma range of products is constantly being evaluated for enhancement and improvement to make sure the level of quality and performance is as expected.