



4.1 6,000kg SNATCH STRAP PRODUCT INFORMATION SHEET

"Don't get caught out, without this essential 4WD recovery gear"



Snatch Strap with 'Wrap-it' Strap

FEATURES

- **Easy Strap Identification**
- **Strap usage recording tag**
- **'Wrap-it' Strap**
- **Lower Rating**

The 6,000kg Snatch Strap has the strap type and load rating printed on each eyelet to ensure ease of identification and use.

Located with the compliance tags, the usage tags allows you to record and track the number of times the strap is used to help identify fatigue and age of the strap.

New easy storage Wrap it Strap, stitched to the snatch strap so it is ready to roll out and use anytime. Then just roll it back up and it is ready for the next use.

Designed specifically to suit the lighter vehicles in the 4WD and Compact SUV range, ensuring the strap stretched correctly reducing shock loading on the vehicle.

SPECIFICATIONS

Part Number	52X02	Warranty	1 Year 'No-Fuss' Warranty
Materials	Nylon Webbing	Dimensions	9 metres long x 60mm wide (unstretched)
Capacity	6,000kg	Stretch Factor	20%
Weight	1.6kg	Colour	Grey with Red Ends Printed with identification
Please Note	The minimum breaking strength of the strap should be between 2 and 3 times the vehicle's Gross Vehicle Mass (GVM).		

Please turn over for Care and Safety Instructions...



4.1 6,000kg SNATCH STRAP PRODUCT INFORMATION SHEET

“Don’t get caught out, without this essential 4WD recovery gear”

CARE AND SAFETY

Please Note: The minimum breaking strength of the strap should be between 2 and 3 times the vehicle’s Gross Vehicle Mass (GVM).

Please read the 'Safety Standard for Motor Vehicle Recovery Straps' enclosed in the product.

Clean snatch strap in warm water and allow to dry in the shade. (Always ensure snatch strap is dry prior to being stored)

Snatch strap life = 10 vehicle recoveries or as per safety & inspection requirements above.

Kingsley Enterprises highly recommends that all usages of the snatch strap be recorded and kept with the off road recovery kit.

Prior to using the snatch strap inspect for damage.

Damage may include:

- Frayed materials
- Loose stitching
- Cuts & abrasions

If the snatch strap exhibits any of the above discard the snatch strap. Do not expose snatch strap to any petroleum based products, acids or alkaline products.

Ensure snatch strap is not stored in direct sunlight or wet/humid environments.

Exceeding the capacity of this product will cause it to fail.

DO NOT attach this strap to a tow ball, bullbar, ONLY use dedicated tow points as described in vehicle manual.

All spectators to be at least 20m from vehicles during recovery.

Avoid connecting straps to form longer components.

Never push a vehicle during recovery.