



4.1 SNATCH STRAP PRODUCT INFORMATION SHEET

"Don't get caught out, without this essential 4WD recovery gear"



SPECIFICATIONS

Part Number	52X00
Materials	All nylon stretch webbing
Dimensions	9 metres long x 50mm wide (Plus 22% Stretch Factor)
Capacity	Fully Australian tested past 8,000kg breaking capacity
Weight	1.7kg
Warranty	5 year No-Fuss warranty

Part Number	52X01
Materials	All nylon stretch webbing
Dimensions	9 metres long x 50mm wide (Plus 20% Stretch Factor)
Capacity	Fully Australian tested past 11,000kg breaking capacity
Weight	2.6kg
Warranty	1 year No-Fuss warranty

VEHICLE APPLICATIONS

Used to pull a vehicle out of a bogged situation when a tow vehicle is available.

PRODUCT TIPS

- Essential piece of 4WD recovery gear
- Allow 15-30 minutes between each use for fibres to contract and regain their elasticity (Note: it is the elasticity of the Strap that does the work when retrieving a bogged vehicle.)
- Made from a white material to allow ease of identification of corrosive contaminants and damage.

Continued over page...



4.1 SNATCH STRAP PRODUCT INFORMATION SHEET

"Don't get caught out, without this essential 4WD recovery gear"

SAFETY PRECAUTIONS

- Before you try to move the vehicle, assess the terrain you need to cross to get to safety, and consolidate the track with saplings or scrub if necessary
- Never attach strap to either vehicle by simply hooking over a tow bar or bull bar; always attach to a tow hook or ring using a bow shackle of a rating no less than 3¼ tonne.
- Do not allow the strap to be abused by abrasion across rocks or suffer nicks or cuts as this will reduce the Snatch Straps' strength and capacity and will lower it's rating.
- Make sure all spectators and passengers are well away from the vehicles and not directly in front or behind the vehicles about to be recovered.