



C10000 NH

10 000LB HYDRAULIC WINCH

Compact, tough. A hydraulic winch for industrial and commercial applications. The unique patented steel gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range. Complete with internal brake to ensure maximum control and load holding. Stainless steel roller fairleads and fittings are standard.



STANDARD ACCESSORIES

- 26m x 11mm steel cable
- Heavy Duty Roller Fairlead
- 5/16 Hook

OUTSTANDING FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Stainless Steel fairlead and Fittings
- Rugged and compact for Long Life

SPECIFICATION

RATED LINE PULL: 10 000lbs (4536kg)
MAX LINE PULL: 12 500lbs (5670kg)
MOTOR: Hydraulic Dis 50 ml/r
GEARING: 33:1
DRUM SIZE Dia x L: 72 x 224mm
CABLE Dia x L: 10.2mm x 26.5m
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 510 x 186 x 224mm
WEIGHT: 55kg

TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)
1	10000 (4536)
2	8020 (3638)
3	6700 (3039)
4	5800 (2631)

Line pull lbs (kg)	Line speed ft/min	Line speed m/min	Flow l/min	Press Bar
0	10	2.8	20	25
6000 (2727)	15	4.6	30	70
10000 (4545)	26	7.6	50	130