



C9500 HS

PERFORMANCE - HIGH SPEED ELECTRIC WINCH

The ultimate winch for Extreme Terrain. Fully Sealed with an unbeatable line Speed of 65 ft/min. Outstanding features includes Huge 6.5 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing. Complete with heavy duty integrated wireless remote.

**FULLY
SEALED**

NO LOAD SPEED OF 65FT/MIN



**WIRELESS
CONTROL**



STANDARD ACCESSORIES

- Dyneema Synthetic rope 9.5mm X 30m
- 3m Remote Handset
- Aluminium Fairlead
- Heavy Duty Battery Leads
- Isolation switch
- Stainless Steel Mounting hardware
- Built In Wireless remote
- 5/16 hook

OUTSTANDING FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover for Added Protection
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Integrated Wireless Remote

** Fairlead does not attach direct to the winch **

SPECIFICATION

RATED LINE PULL: 9500lbs (4500kg)
MOTOR: 12v : 6.5hp / 4.5kw
GEARING: 110:1
BRAKING ACTION: Automatic in the drum
DRUM SIZE Dia x L: 63 x 224mm
CABLE Dia x L: 9.5mm x 30m
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 577 x 160 x 215mm

TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)	Line pull		Line speed		Amp draw	
		lbs (kg)	ft/min	m/min	12v	24v	
1	9500 (4309)	0	65	19.8	80	45	
2	7706 (3495)	4000 (1818)	12.5	3.8	300	175	
3	6482 (2940)	6000 (2722)	11.81	3.6	400	230	
4	5400 (2400)	9500 (4309)	8.86	1.9	530	335	