



C10000 NW

10 000LB HYDRAULIC WINCH

Compact, tough. A hydraulic winch for industrial and commercial applications. The special heat treated planetary gearing system combined with a highly efficient and powerful hydraulic motor ensures maximum performance over the full load range. Complete with internal brake to ensure maximum control and load holding.



STANDARD ACCESSORIES

- 26m x 11mm steel cable
- 5/16 Hook
- Tensioner included

OUTSTANDING FEATURES

- Patented Heavy Duty Gearing
- Integral, Automatic Failsafe Brake
- Spring Engaged Manual Freespool
- Rugged and Compact for Long Life
- Meets the requirements of EN 14492.1

SPECIFICATION

RATED LINE PULL: 10 000lbs (4536kg)
MAX LINE PULL: 12 500lbs (5670kg)
MOTOR: Hydraulic Dis 100.8 ml/r
GEARING: 16:1
DRUM SIZE Dia x L: 102 x 253mm
CABLE Dia x L: 11mm x 26.5m
MOUNTING PATTERN: 374.2 x 114.3mm
(291 x 117.2mm)
DIMENSIONS: 643 x 265 x 241mm

TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)
1	10000 (4536)
2	7355 (3339)
3	6780 (3078)
4	5711 (2952)

Line pull lbs (kg)	Line speed ft/min	Line speed m/min	Flow l/min	Press Mpa
0	2.97	0.9	5	2
3995 (1816)	5.94	1.8	10	5.6
5992 (2724)	11.88	3.6	20	8.4
7990 (3632)	23.76	7.2	40	11.2
10000 (4536)	36.96	11.2	60	13.8