



C9500 HS SAVIURA

HIGH SPEED ELECTRIC WINCH



The ultimate winch for Extreme Terrain. Fully Sealed with an unbeatable line Speed of 65 ft/min. Outstanding features includes Huge 6.5 hp high quality double sealed motor with brass fittings, heavy duty waterproof contactors, double sealed drum on maintenance free bearings, quiet, fully sealed efficient full steel planetary gearing. Stainless steel roller fairlead and fittings as standard. Complete with heavy duty integrated wireless remote.

FULLY SEALED 600 AMP CONTACTORS



WIRELESS CONTROL

LASER ETCHED EXTRUDED ALUMINIUM TIE BARS REINFORCED WITH STEEL BODY

NO LOAD SPEED OF 65FT/MIN

FULLY SEALED TO IP 68 STANDARD

NEW HEAVY DUTY GLOSS CHIP RESISTANT FINISH



STANDARD ACCESSORIES

- 26m x 9.5mm steel cable
 - 3m Remote Handset
 - Heavy Duty Stainless Steel Fairlead
 - Heavy Duty Battery Leads
 - Isolation switch
 - Stainless Steel Mounting hardware
 - Built In Wireless remote
 - 5/16 hook
- Synthetic Rope and Aluminium fairlead option.

OUTSTANDING FEATURES

- All Brass (no corrosion) Series Wound Motor
- Double Sealed Motor
- Sealed Waterproof Contactor
- Steel Contactor Cover for Added Protection
- Double Sealed Drum (Gearbox/Motor)
- Sealed 3 Stage Planetary Gears
- Stainless Steel 4 Way fairleads
- Integrated Wireless Remote

SPECIFICATION

RATED LINE PULL: 9500lbs (4500kg)
MOTOR: 12v : 6.5hp / 4.5kw
GEARING: 110:1
BRAKING ACTION: Automatic in the drum
DRUM SIZE Dia x L: 63 x 224mm
CABLE Dia x L: 9.5mm x 26m
MOUNTING PATTERN: 254 x 114.3mm
DIMENSIONS: 577 x 160 x 215mm

TECHNICAL PERFORMANCE

Layer of wire rope	Line pull lbs (kg)
1	9500 (4309)
2	7706 (3495)
3	6482 (2940)
4	5400 (2400)

Line pull lbs (kg)	Line speed		Amp draw	
	ft/min	m/min	12v	24v
0	65	19.8	80	45
4000 (1818)	12.5	3.8	300	175
6000 (2722)	11.81	3.6	400	230
9500 (4309)	8.86	1.9	530	335