

H-EN SERIES

EN 14492:1 COMPLIANT HYDRAULIC WINCHES



The H-EN Series hydraulic winches meet EN14992 & SAE J-706 standards. They provide you with continuous duty and will fulfill all your industrial winching requirements. They are designed for tough, commercial, industrial applications and are available in a full range of planetary gear with capabilities from 8000 to 20000 pounds.



OUTSTANDING FEATURES

- Highly efficient, long lifetime hydraulic motor.
- Automatic multidisc hydraulic brake ensure no heat to drum.
- Dual balance valve & 360 degree rotatable gearbox enables the winch to be mounted in various positions.
- Synthetic Rope can be used.
- Reliable high strength alloy gear set.

TECHNICAL SPECIFICATIONS & PRICES

PART NO:	DESCRIPTION:	Prices £:			
		RRP	1-5	6-9	10+
80NVSHY	8000 lb EN HYDRAULIC WINCH complete with Balance valve	750	550	490	460
10NVSHY	10000 lb EN HYDRAULIC WINCH complete with Balance valve	790	600	530	510
15NVSHY	15000 lb EN HYDRAULIC WINCH complete with Balance valve	865	645	600	585
ACCESSORIES FOR H-EN HYDRAULIC WINCHES					
WIR90EN	9.2mm X 35M steel cable with hook for 80NVSHY	45	39	36	33
WIR10EN	10mm X 30M steel cable with hook for 10NVSHY	50	43	38	34
WIR20EN	13mm X 30M steel cable with hook for 15NVSHY	80	70	65	60
RFNHHY0	ROLLER FAIRLEAD FOR 8000LB - 15000LB H-EN HYDRAULIC WINCH	25	20	17	13
TEN0100	TENSIONER FOR H-EN 8000LB AND 10000LB	25	19	16	13
TEN0150	TENSIONER FOR H-EN 15000LB	30	25	21	18
ISTEN10	INSTALLATION PLATE FOR H-EN 8000LB AND 10000LB	45	40	35	30
ISTEN15	INSTALLATION PLATE FOR H-EN 15000LB	55	45	40	35